

SPECTRO LUBRICANT TECHNICAL DATA

Heavy Duty Engine Oil



- EXCEPTIONALLY HIGH ANTI-WEAR ADDITIVE TREATMENT REDUCES WEAR.
- MULTI-GRADE 20W50 FOR TEMPS ABOVE 30° F
- MULTI-GRADE 25W60 FOR TEMPS ABOVE 40° F
- SAE GRADE 50 FOR TEMPS ABOVE 60° F
- SAE GRADE 60 FOR TEMPS ABOVE 80° F
- SUPER HEAVY GRADE 70 FOR TEMPS ABOVE 85° F
- ELIMINATES VALVE STICKING FROM CARBON DEPOSITS.
- MEETS ALL KNOWN OEM WARRANTY REQUIREMENTS.
- API SF/SG – CD/CG-4

Description

Spectro Heavy Duty is superior motor lubricant formulated specifically for use in American-built Harley® V-Twin engines. Crafted from premium petroleum base oils combined with the most advanced anti-wear, anti-carbon additive systems available, Spectro Heavy Duty extends component life, reduces wear, eliminates valve sticking. Meets all known OEM warranty requirements.

Application

Heavy Duty oils should be used according to the manufacturer's recommended change intervals and viscosity. They may be used in all Harley® engines, any year, without restriction, and will not void and factory warranty

Typical Inspections	20w50	25w60
Kinematic Viscosity @ 210° F SSU	93	120
Kinematic Viscosity @ 100° F SSU	820	1200
Flash Point, °F	417	433
Pourpoint, °F	-10	-5
Gravity @ 60°	28.5	27.4

Typical Inspections	50	60	70
Kinematic Viscosity @ 210° F SSU	105	140	160
Kinematic Viscosity @ 100° F SSU	1150	1675	2532
Flash Point, °F	390	410	410
Pourpoint, °F	-5	15	20
Gravity @ 60°	27.3	27	26.8

Code	Description	Weight
R.HD2050	12/1 Quart Bottles	25 Lbs.
R.HD2560	12/1 Quart Bottles	25 Lbs.
R.HD50	12/1 Quart Bottles	25 Lbs.
R.HD60	12/1 Quart Bottles	25 Lbs.
R.HD70	12/1 Quart Bottles	25 Lbs.
T.HD2050	4/1 Gal Bottles	33 Lbs.
Z.HD2050	55 Gal Drum	450 Lbs.

SPECTRO OILS OF AMERICA
993 Federal Rd., Brookfield, CT 06804
203-775-1291 Fax 203-775-8720
www.spectro-oils.com

