

SPECTRO LUBRICANT TECHNICAL DATA

SPECTRO MARINE EXTREME PERSONAL WATERCRAFT



- MEETS ALL KNOWN WATERCRAFT MANUFACTURERS' WARRANTY REQUIREMENTS AND RECOMMENDATIONS.
- EXCEEDS JASO FC, ISO-L-EGD+ AND A.P.I. TC TEST REQUIREMENTS.
- UNSURPASSED IN CLEANLINESS AND LOW SMOKE EMISSIONS.
- HIGHEST LUBRICITY AND TORQUE INDEXES.
- FOR USE IN ALL TWO-CYCLE ARTIC-CAT, POLARIS, YAMAHA, KAWASAKI AND SEA-DOO PERSONAL WATERCRAFT ENGINES, ANY YEAR, WITHOUT RESTRICTION

Description

Spectro Marine Extreme Full Synthetic PWC is the ultimate two-cycle lubricant formulated specifically for use in modern two-cycle watercraft. A fully synthetic formulation with breakthrough additive technology (polybutenes, borated polyisobutenyl succinic anhydride nitrogen functionalized dispersant, mixed calcium alkylaryl detergent) combines to provide virtually smokeless operation and residue-free engine cleanliness. No oil anywhere burns cleaner than this JASO FC + ISO-EGD PLUS oil.

Application

Spectro Marine Extreme Full Synthetic is formulated specifically for use in all modern, two-cycle watercraft regardless of make or model.

For Racing Use

Spectro Marine extreme Full Synthetic can be mixed at the manufacturers' recommended ratio or used in injector systems. Otherwise, mix thoroughly at a 50:1 fuel to oil ratio (2.5 ounces per gallon, 12.5 oz to five gallons). No special steps need to be taken when switching to Spectro Marine Extreme Full Synthetic.

Typical Inspections

Specific Gravity @ 60/60° F	0.888
Kinematic Viscosity @ 100° C cST	9.46
Kinematic Viscosity @ 40° C cST	57.1
Flash Point, °C	88
Pourpoint, °C	-57
Sulfated Ash, Wt %	0.10

Code

T.SYNPWC

Description

4/1 Gallon Bottles

Weight

33 Lbs.

SPECTRO OILS OF AMERICA
993 Federal Rd., Brookfield, CT 06804
203-775-1291 Fax 203-775-8720
www.spectro-oils.com

2.28.2010

